


KLLVSB

Courbe articulée pour KLL



A fixer avec:



Boulon et écrou autobloquant
VM

| Référence | Finition | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unité |
|------------------------|----------|---------|---------|------------|---------|--------|---|-------|
| KLLVSB60.150 | - | 60 | 150 | | 1040 | 2,705 | 1 | STK |
| KLLVSB60.200 | - | 60 | 200 | | 1040 | 2,822 | 1 | STK |
| KLLVSB60.300 | - | 60 | 300 | | 1040 | 3,057 | 1 | STK |
| KLLVSB60.400 | - | 60 | 400 | | 1040 | 3,291 | 1 | STK |
| KLLVSB60.450 | - | 60 | 450 | | 1040 | 3,408 | 1 | STK |
| KLLVSB60.500 | - | 60 | 500 | | 1040 | 3,525 | 1 | STK |
| KLLVSB60.600 | - | 60 | 600 | | 1040 | 3,759 | 1 | STK |
| KLLVSB60.750 | SZ | 60 | 750 | 0,90/1,25 | 1000 | 4,110 | 1 | STK |
| KLLVSB60.800 | SZ | 60 | 800 | 0,90/1,25 | 1000 | 4,227 | 1 | STK |
| KLLVSB60.900 | SZ | 60 | 900 | 0,90/1,25 | 1000 | 4,461 | 1 | STK |
| KLLVSB110.150 | - | 110 | 150 | | 1090 | 5,292 | 1 | STK |
| KLLVSB110.200 | - | 110 | 200 | | 1090 | 5,409 | 1 | STK |
| KLLVSB110.300 | - | 110 | 300 | | 1090 | 5,644 | 1 | STK |
| KLLVSB110.400 | - | 110 | 400 | | 1090 | 5,878 | 1 | STK |
| KLLVSB110.450 | - | 110 | 445 | | 1090 | 5,995 | 1 | STK |
| KLLVSB110.500 | - | 110 | 500 | | 1090 | 6,112 | 1 | STK |
| KLLVSB110.600 | - | 110 | 600 | | 1090 | 6,346 | 1 | STK |
| KLLVSB110.750 | SZ | 110 | 750 | 1,25 | 1000 | 6,697 | 1 | STK |
| KLLVSB110.800 | SZ | 110 | 800 | 1,25 | 1000 | 6,814 | 1 | STK |
| KLLVSB110.900 | SZ | 110 | 900 | 1,25 | 1000 | 7,048 | 1 | STK |
| ZMKLLVSB60.150 | DF | 60 | 150 | 0,90/1,25 | 1000 | 2,705 | 1 | STK |
| ZMKLLVSB60.200 | DF | 60 | 200 | 0,90/1,25 | 1000 | 2,822 | 1 | STK |
| ZMKLLVSB60.300 | DF | 60 | 300 | 0,90/1,25 | 1000 | 3,057 | 1 | STK |
| ZMKLLVSB60.400 | DF | 60 | 400 | 0,90/1,25 | 1000 | 3,291 | 1 | STK |
| ZMKLLVSB60.450 | DF | 60 | 450 | 0,90/1,25 | 1000 | 3,408 | 1 | STK |
| ZMKLLVSB60.500 | DF | 60 | 500 | 0,90/1,25 | 1000 | 3,525 | 1 | STK |
| ZMKLLVSB60.600 | DF | 60 | 600 | 0,90/1,25 | 1000 | 3,759 | 1 | STK |
| ZMKLLVSB60.750 | DF | 60 | 750 | 0,90/1,25 | 1000 | 4,110 | 1 | STK |
| ZMKLLVSB60.800 | DF | 60 | 800 | 0,90/1,25 | 1000 | 4,227 | 1 | STK |
| ZMKLLVSB60.900 | DF | 60 | 900 | 0,90/1,25 | 1000 | 4,461 | 1 | STK |
| ZMKLLVSB110.150 | DF | 110 | 150 | 1,25 | 1000 | 5,292 | 1 | STK |
| ZMKLLVSB110.200 | DF | 110 | 200 | 1,25 | 1000 | 5,409 | 1 | STK |
| ZMKLLVSB110.300 | DF | 110 | 300 | 1,25 | 1000 | 5,644 | 1 | STK |
| ZMKLLVSB110.400 | DF | 110 | 400 | 1,25 | 1000 | 5,878 | 1 | STK |
| ZMKLLVSB110.450 | DF | 110 | 450 | 1,25 | 1000 | 5,995 | 1 | STK |
| ZMKLLVSB110.500 | DF | 110 | 500 | 1,25 | 1000 | 6,112 | 1 | STK |
| ZMKLLVSB110.600 | DF | 110 | 600 | 1,25 | 1000 | 6,346 | 1 | STK |
| ZMKLLVSB110.750 | DF | 110 | 750 | 1,25 | 1000 | 6,697 | 1 | STK |
| ZMKLLVSB110.800 | DF | 110 | 800 | 1,25 | 1000 | 6,814 | 1 | STK |
| ZMKLLVSB110.900 | DF | 110 | 900 | 1,25 | 1000 | 7,048 | 1 | STK |

Nombre minimal des boulons et des écrous VM6.10: 8 pièces.

Légende de la finition

- SZ = Sendzimir
- DF = Defender