

KLM100B45

Courbe horizontale à 45° pour KLM100



A fixer avec:



Boulon à collet
(DIN 603)
RBK

Ecroû elargi (DIN
6923)
RM

Rayon: 600 mm

| Référence | Finition | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unité |
|-------------------------|----------|---------|---------|------------|---------|--------|---|-------|
| KLM100B45.150 | SZ | 100 | 158 | | | 3,412 | 1 | STK |
| KLM100B45.200 | SZ | 100 | 208 | | | 3,628 | 1 | STK |
| KLM100B45.300 | SZ | 100 | 308 | | | 4,060 | 1 | STK |
| KLM100B45.400 | SZ | 100 | 408 | | | 4,493 | 1 | STK |
| KLM100B45.450 | SZ | 100 | 458 | | | 4,709 | 1 | STK |
| KLM100B45.500 | SZ | 100 | 508 | | | 5,283 | 1 | STK |
| KLM100B45.600 | SZ | 100 | 608 | | | 5,792 | 1 | STK |
| KLM100B45.750 | SZ | 100 | 758 | | | 6,556 | 1 | STK |
| KLM100B45.800 | SZ | 100 | 808 | | | 6,811 | 1 | STK |
| KLM100B45.900 | SZ | 100 | 908 | | | 7,320 | 1 | STK |
| KLM100B45.1000 | SZ | 100 | 1008 | | | 8,571 | 1 | STK |
| ZMKLM100B45.150 | DF | 100 | 158 | | | 3,412 | 1 | STK |
| ZMKLM100B45.200 | DF | 100 | 208 | | | 3,628 | 1 | STK |
| ZMKLM100B45.300 | DF | 100 | 308 | | | 4,060 | 1 | STK |
| ZMKLM100B45.400 | DF | 100 | 408 | | | 4,493 | 1 | STK |
| ZMKLM100B45.450 | DF | 100 | 458 | | | 4,709 | 1 | STK |
| ZMKLM100B45.500 | DF | 100 | 508 | | | 5,283 | 1 | STK |
| ZMKLM100B45.600 | DF | 100 | 608 | | | 5,792 | 1 | STK |
| ZMKLM100B45.750 | DF | 100 | 758 | | | 6,556 | 1 | STK |
| ZMKLM100B45.800 | DF | 100 | 808 | | | 6,811 | 1 | STK |
| ZMKLM100B45.900 | DF | 100 | 908 | | | 7,320 | 1 | STK |
| ZMKLM100B45.1000 | DF | 100 | 1008 | | | 8,571 | 1 | STK |

Nombre minimal des boulons et des écrous: 8 pièces.

Légende de la finition

- SZ = Sendzimir
- DF = Defender