

# SLOS


## Cloison de séparation séparée



| Référence          | Finition | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/m  | 📦   | Unité |
|--------------------|----------|---------|---------|------------|---------|-------|-----|-------|
| <b>SLOS35</b>      | SZ       | 28      |         |            | 3000    | 0,330 | 150 | M     |
| <b>SLOS60</b>      | SZ       | 53      |         |            | 3000    | 0,511 | 120 | M     |
| <b>SLOS60.2000</b> | -        | 53      |         |            | 1900    | 0,793 | 520 | M     |
| <b>SLOS85</b>      | SZ       | 78      |         |            | 3000    | 0,680 | 60  | M     |
| <b>SLOS110</b>     | SZ       | 103     |         |            | 3000    | 0,820 | 30  | M     |
| <b>ZMSLOS35</b>    | DF       | 28      |         |            | 3000    | 0,257 | 150 | M     |
| <b>ZMSLOS60</b>    | DF       | 60      |         |            | 3000    | 0,397 | 120 | M     |
| <b>ZMSLOS85</b>    | DF       | 78      |         |            | 3000    | 0,529 | 60  | M     |
| <b>ZMSLOS110</b>   | DF       | 103     |         |            | 3000    | 0,638 | 30  | M     |

### A fixer avec:

Matériel de fixation: 1 par mètre.



Boulon à tête  
ronde  
autobloquant  
RB

Ecrou coulissant  
pour profil  
support  
PNP06-  
PNP12A

### Légende de la finition

- SZ = Sendzimir
- DF = Defender