


KLM125SB45

Courbe intérieure pour KLM125

Rayon: 600 mm



A fixer avec:



Boulon à collet
(DIN 603)
RBK

Ecoure elargi (DIN
6923)
RM

| Référence | Finition | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unité |
|--------------------------|----------|---------|---------|------------|---------|--------|---|-------|
| KLM125SB45.150 | SZ | 125 | 158 | | | 3,284 | 1 | STK |
| KLM125SB45.200 | SZ | 125 | 208 | | | 3,400 | 1 | STK |
| KLM125SB45.300 | SZ | 125 | 308 | | | 3,630 | 1 | STK |
| KLM125SB45.400 | SZ | 125 | 408 | | | 3,860 | 1 | STK |
| KLM125SB45.450 | SZ | 125 | 458 | | | 3,976 | 1 | STK |
| KLM125SB45.500 | SZ | 125 | 508 | | | 4,091 | 1 | STK |
| KLM125SB45.600 | SZ | 125 | 608 | | | 4,321 | 1 | STK |
| KLM125SB45.750 | SZ | 125 | 758 | | | 4,667 | 1 | STK |
| KLM125SB45.800 | SZ | 125 | 808 | | | 4,782 | 1 | STK |
| KLM125SB45.900 | SZ | 125 | 908 | | | 5,012 | 1 | STK |
| KLM125SB45.1000 | SZ | 125 | 1008 | | | 5,243 | 1 | STK |
| ZMKLM125SB45.150 | DF | 125 | 158 | | | 3,284 | 1 | STK |
| ZMKLM125SB45.200 | DF | 125 | 208 | | | 3,400 | 1 | STK |
| ZMKLM125SB45.300 | DF | 125 | 308 | | | 3,630 | 1 | STK |
| ZMKLM125SB45.400 | DF | 125 | 408 | | | 3,860 | 1 | STK |
| ZMKLM125SB45.450 | DF | 125 | 458 | | | 3,976 | 1 | STK |
| ZMKLM125SB45.500 | DF | 125 | 508 | | | 4,091 | 1 | STK |
| ZMKLM125SB45.600 | DF | 125 | 608 | | | 4,321 | 1 | STK |
| ZMKLM125SB45.750 | DF | 125 | 758 | | | 4,667 | 1 | STK |
| ZMKLM125SB45.800 | DF | 125 | 808 | | | 4,782 | 1 | STK |
| ZMKLM125SB45.900 | DF | 125 | 908 | | | 5,012 | 1 | STK |
| ZMKLM125SB45.1000 | DF | 125 | 1008 | | | 5,243 | 1 | STK |

Nombre minimal des boulons et des écrous: 8 pièces.

Légende de la finition

- SZ = Sendzimir
- DF = Defender