

# KLZSB

## Courbe intérieure pour KLZ



### A fixer avec:



Boulon à collet  
(DIN 603)  
RBK

Ecoux elargi (DIN  
6923)  
RM

Rayon: 600 mm

Référence	Finition	↑ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Unité
<b>KLZSB150</b>	SZ	150	150			5,940	1	STK
<b>KLZSB200</b>	SZ	150	208			6,093	1	STK
<b>KLZSB300</b>	SZ	150	308			6,400	1	STK
<b>KLZSB400</b>	SZ	150	408			6,707	1	STK
<b>KLZSB500</b>	SZ	150	508			7,015	1	STK
<b>KLZSB600</b>	SZ	150	608			7,322	1	STK
<b>KLZSB800</b>	-	150	800			7,937	1	STK
<b>KLZSB1000</b>	-	150	1000			8,552	1	STK
<b>ZMKLZSB150</b>	DF		150			5,940	1	STK
<b>ZMKLZSB200</b>	DF	150	208			6,093	1	STK
<b>ZMKLZSB300</b>	DF	150	308			6,400	1	STK
<b>ZMKLZSB400</b>	DF	150	408			6,707	1	STK
<b>ZMKLZSB450</b>	DF	150	450			6,862	1	STK
<b>ZMKLZSB500</b>	DF	150	508			7,015	1	STK
<b>ZMKLZSB600</b>	DF	150	608			7,322	1	STK
<b>ZMKLZSB800</b>	-		800			7,937	1	STK
<b>ZMKLZSB1000</b>	-		1000			8,552	1	STK
<b>PEKLZSB150</b>	-	150	150			5,940	1	STK
<b>PEKLZSB800</b>	-	150	800			7,937	1	STK
<b>PEKLZSB1000</b>	-	150	1000			8,552	1	STK

Nombre minimal des boulons et des écrous: 8 pièces.

### Légende de la finition

- SZ = Sendzimir
- DF = Defender