

## D Couvercle universel



Pour cheminements horizontaux et verticaux.  
Couvercle avec un bord de 10 mm.

### A fixer avec:



Attache couvercle  
encliquetable  
DCLVF35



Attache couvercle  
encliquetable  
DCLVF

Référence	Finition	↑ mm	↔ mm	→  ← mm	↔ mm	kg/m		Unité
<b>D050</b>	SZ	10	50		3000	0,328	30	M
<b>D075</b>	SZ	10	75		2000	0,446	20	M
<b>D100</b>	SZ	10	100		2000	0,564	20	M
<b>D100.3</b>	SZ	10	100		3000	0,563	300	M
<b>D150</b>	SZ	10	150		2000	0,799	20	M
<b>D200</b>	DF	10	200		2000	1,035	20	M
<b>D200.3</b>	SZ	10	200		3000	1,035	300	M
<b>D250</b>	SZ	10	250		2000	1,481	20	M
<b>D300</b>	SZ	10	300		2000	1,756	20	M
<b>D400</b>	SZ	10	400		2000	2,960	20	M
<b>D450</b>	SZ	10	452	0,90	2000	3313	2	M
<b>D500</b>	SZ	10	500		2000	3,667	2	M
<b>D600</b>	SZ	10	600		2000	4,373	2	M
<b>D750</b>	SZ	10	752	1,25	2000	7537	2	M
<b>D800</b>	SZ	10	802	1,25	2000	8028	2	M
<b>D900</b>	SZ	10	902	1,25	2000	9009	2	M
<b>ZMD050</b>	DF	10	50		3000	0,328	30	M
<b>ZMD075</b>	DF	10	75		2000	0,446	20	M
<b>ZMD100</b>	DF	10	100		2000	0,564	20	M
<b>ZMD150</b>	DF	10	150		2000	0,799	20	M
<b>ZMD200</b>	DF	10	200		2000	1,035	20	M
<b>ZMD250</b>	DF	10	250		2000	1,481	20	M
<b>ZMD300</b>	DF	10	300		2000	1,756	20	M
<b>ZMD450</b>	DF	10	452	0,90	2000	3313	2	M
<b>ZMD400</b>	DF	10	400		2000	2,960	20	M
<b>ZMD500</b>	DF	10	500		2000	3,667	2	M
<b>ZMD600</b>	DF	10	600		2000	4,373	2	M
<b>ZMD750</b>	DF	10	752	1,25	2000	7537	2	M
<b>ZMD800</b>	DF	10	802	1,25	2000	8028	2	M
<b>ZMD900</b>	DF	10	902	1,25	2000	9009	2	M
<b>PED450</b>	PE	10	452	0,90	2000	3313	2	M
<b>PED750</b>	PE	10	752	1,25	2000	7537	2	M
<b>PED800</b>	PE	10	802	1,25	2000	8028	2	M
<b>PED900</b>	PE	10	902	1,25	2000	9009	2	M

Pour des largeurs > 400 mm: le couvercle est pourvu de nervures de renfort.

### Légende de la finition

- SZ = Sendzimir
- DF = Defender
- PE =