


D Couvercle universel



Pour cheminements horizontaux et verticaux

Référence	Finition	↑ mm	↔ mm	→ ← mm	↔ mm	kg/m		Unité
D050	SZ	10	50		3000	0,328	30	M
D075	SZ	10	75		2000	0,446	20	M
D100	SZ	10	100		2000	0,564	20	M
D100.3	SZ	10	100		3000	0,563	300	M
D150	SZ	10	150		2000	0,799	20	M
D200	DF	10	200		2000	1,035	20	M
D200.3	SZ	10	200		3000	1,035	300	M
D250	SZ	10	250		2000	1,481	20	M
D300	SZ	10	300		2000	1,756	20	M
D400	SZ	10	400		2000	2,960	20	M
D500	SZ	10	500		2000	3,667	2	M
D600	SZ	10	600		2000	4,373	2	M
ZMD050	DF	10	50		3000	0,328	30	M
ZMD075	DF	10	75		2000	0,446	20	M
ZMD100	DF	10	100		2000	0,564	20	M
ZMD150	DF	10	150		2000	0,799	20	M
ZMD200	DF	10	200		2000	1,035	20	M
ZMD250	DF	10	250		2000	1,481	20	M
ZMD300	DF	10	300		2000	1,756	20	M
ZMD400	DF	10	400		2000	2,960	20	M
ZMD500	DF	10	500		2000	3,667	2	M
ZMD600	DF	10	600		2000	4,373	2	M

A fixer avec:



Attache couvercle
DCL

Attache couvercle
imperdable
DCO

Pour des largeurs > 400 mm: le couvercle est pourvu de nervures de renfort.

Légende de la finition

- SZ = Sendzimir
- DF = Defender