

SLOS Cloison de séparation séparée



| | | ‡ | \leftrightarrow | $\rightarrow \parallel \leftarrow$ | \rightleftharpoons | | ^ | |
|-------------|----------|----------|-------------------|------------------------------------|----------------------|-------|----------|-------|
| Référence | Finition | mm | mm | mm | mm | kg/m | Θ | Unité |
| SLOS35 | SZ | 28 | | | 3000 | 0,330 | 150 | М |
| SLOS60 | SZ | 53 | | | 3000 | 0,511 | 120 | М |
| SLOS60.2000 | - | 53 | | | 1900 | 0,848 | 520 | М |
| SLOS85 | SZ | 78 | | | 3000 | 0,680 | 60 | М |
| SLOS110 | SZ | 103 | | | 3000 | 0,820 | 30 | М |
| ZMSLOS35 | DF | 28 | | | 3000 | 0,257 | 150 | М |
| ZMSLOS60 | DF | 60 | | | 3000 | 0,397 | 120 | М |
| ZMSLOS85 | DF | 78 | | | 3000 | 0,529 | 60 | М |
| ZMSLOS110 | DF | 103 | | | 3000 | 0,638 | 30 | М |

A fixer avec:





Boulon et écrou autobloquant VM

Ecrou autobloquant et boulon à collet VMK

Légende de la finition

Matériel de fixation: 1 par mètre

-SZ = Sendzimir

- DF = Defender