


KLLX

Pièce en croix pour KLL



Rayon: 300 mm

| | | | | | | |
|---|------|------|------|------|------|------|
| | 150 | 200 | 300 | 400 | 500 | 600 |
| A | 1021 | 1071 | 1171 | 1271 | 1371 | 1471 |

A fixer avec:



Boulon et écrou autobloquant VM6.10

| Référence | Finition | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unité |
|----------------------|----------|---------|---------|------------|---------|--------|---|-------|
| KLLX60.150 | - | 60 | 141 | | | 3,131 | 1 | STK |
| KLLX60.200 | - | 60 | 191 | | | 3,232 | 1 | STK |
| KLLX60.300 | - | 60 | 291 | | | 4,421 | 1 | STK |
| KLLX60.400 | - | 60 | 391 | | | 4,875 | 1 | STK |
| KLLX60.450 | - | 60 | 443 | | | 5,102 | 1 | STK |
| KLLX60.500 | - | 60 | 491 | | | 5,329 | 1 | STK |
| KLLX60.600 | - | 60 | 591 | | | 5,782 | 1 | STK |
| KLLX60.750 | SZ | 60 | 750 | 1,25 | | 8,530 | 1 | STK |
| KLLX60.800 | SZ | 60 | 800 | 1,25 | | 8,890 | 1 | STK |
| KLLX60.900 | SZ | 60 | 900 | 1,25 | | 9,611 | 1 | STK |
| KLLX110.150 | - | 110 | 145 | | | 4,537 | 1 | STK |
| KLLX110.200 | - | 110 | 195 | | | 4,796 | 1 | STK |
| KLLX110.300 | - | 110 | 295 | | | 5,985 | 1 | STK |
| KLLX110.400 | - | 110 | 395 | | | 6,439 | 1 | STK |
| KLLX110.450 | - | 110 | 445 | | | 6,666 | 1 | STK |
| KLLX110.500 | - | 110 | 495 | | | 6,893 | 1 | STK |
| KLLX110.600 | - | 110 | 595 | | | 7,346 | 1 | STK |
| KLLX110.750 | - | 110 | 750 | | | 8,446 | 1 | STK |
| KLLX110.800 | SZ | 110 | 800 | 1,25 | | 10,408 | 1 | STK |
| KLLX110.900 | - | 110 | 900 | | | 9,546 | 1 | STK |
| ZMKLLX60.150 | DF | 60 | 150 | 1,25 | | 3,985 | 1 | STK |
| ZMKLLX60.200 | DF | 60 | 200 | 1,25 | | 4,258 | 1 | STK |
| ZMKLLX60.300 | DF | 60 | 300 | 1,25 | | 4,965 | 1 | STK |
| ZMKLLX60.400 | DF | 60 | 400 | 1,25 | | 5,570 | 1 | STK |
| ZMKLLX60.450 | DF | 60 | 450 | 1,25 | | 5,872 | 1 | STK |
| ZMKLLX60.500 | DF | 60 | 500 | 1,25 | | 6,451 | 1 | STK |
| ZMKLLX60.600 | DF | 60 | 600 | 1,25 | | 7,113 | 1 | STK |
| ZMKLLX60.750 | DF | 60 | 750 | 1,25 | | 8,530 | 1 | STK |
| ZMKLLX60.800 | DF | 60 | 800 | 1,25 | | 8,890 | 1 | STK |
| ZMKLLX60.900 | DF | 60 | 900 | 1,25 | | 9,611 | 1 | STK |
| ZMKLLX110.150 | DF | 110 | 150 | 1,25 | | 5,502 | 1 | STK |
| ZMKLLX110.200 | DF | 110 | 200 | 1,25 | | 5,775 | 1 | STK |
| ZMKLLX110.300 | DF | 110 | 300 | 1,25 | | 6,483 | 1 | STK |
| ZMKLLX110.400 | DF | 110 | 400 | 1,25 | | 7,087 | 1 | STK |
| ZMKLLX110.450 | DF | 110 | 450 | 1,25 | | 7,390 | 1 | STK |
| ZMKLLX110.500 | DF | 110 | 500 | 1,25 | | 7,969 | 1 | STK |
| ZMKLLX110.600 | DF | 110 | 600 | 1,25 | | 8,631 | 1 | STK |
| ZMKLLX110.750 | DF | 110 | 750 | 1,25 | | 10,047 | 1 | STK |
| ZMKLLX110.800 | DF | 110 | 800 | 1,25 | | 10,408 | 1 | STK |
| ZMKLLX110.900 | DF | 110 | 900 | 1,25 | | 11,129 | 1 | STK |

Nombre minimal des boulons et des écrous VM6.10: 16 pièces.

Légende de la finition

- SZ = Sendzimir
- DF = Defender