

## KLWSB

### Courbe intérieure pour KLW




#### A fixer avec:



Boulon à collet  
(DIN 603)  
RBK

Ecoux elargi (DIN  
6923)  
RM

Rayon: 600 mm

| Référence         | Finition | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk |  | Unité |
|-------------------|----------|---------|---------|------------|---------|--------|---|-------|
| <b>KLWSB200</b>   | SZ       | 200     | 208     |            |         | 7,921  | 1   | STK   |
| <b>KLWSB300</b>   | SZ       | 200     | 308     |            |         | 8,228  | 1   | STK   |
| <b>KLWSB400</b>   | SZ       | 200     | 408     |            |         | 8,535  | 1   | STK   |
| <b>KLWSB500</b>   | SZ       | 200     | 508     |            |         | 8,842  | 1   | STK   |
| <b>KLWSB600</b>   | SZ       | 200     | 608     |            |         | 9,149  | 1   | STK   |
| <b>ZMKLWSB200</b> | DF       | 200     | 208     |            |         | 7,921  | 1   | STK   |
| <b>ZMKLWSB300</b> | DF       | 200     | 308     |            |         | 8,228  | 1   | STK   |
| <b>ZMKLWSB400</b> | DF       | 200     | 408     |            |         | 8,535  | 1   | STK   |
| <b>ZMKLWSB500</b> | DF       | 200     | 508     |            |         | 8,842  | 1   | STK   |
| <b>ZMKLWSB600</b> | DF       | 200     | 608     |            |         | 9,149  | 1   | STK   |

Nombre minimal des boulons et des écrous: 8 pièces.

#### Légende de la finition

- SZ = Sendzimir
- DF = Defender