

KLZT

Pièce en T pour KLZ



A fixer avec:



Boulon à collet
(DIN 603)
RBK

Ecrou elargi (DIN
6923)
RM

Rayon: 600 mm

| | | | | | |
|---|------|------|------|------|------|
| | 200 | 300 | 400 | 500 | 600 |
| A | 1962 | 2062 | 2162 | 2262 | 2362 |

| Référence | Finition | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unité |
|-------------------|----------|---------|---------|------------|---------|--------|---|-------|
| KLZT150 | - | 150 | 150 | | | 14,299 | 1 | STK |
| KLZT200 | SZ | 150 | 208 | | | 14,515 | 1 | STK |
| KLZT300 | SZ | 150 | 308 | | | 15,766 | 1 | STK |
| KLZT400 | SZ | 150 | 408 | | | 16,892 | 1 | STK |
| KLZT500 | SZ | 150 | 508 | | | 18,017 | 1 | STK |
| KLZT600 | SZ | 150 | 608 | | | 20,921 | 1 | STK |
| KLZT800 | - | 150 | 800 | | | 23,432 | 1 | STK |
| KLZT1000 | - | 150 | 1000 | | | 26,680 | 1 | STK |
| ZMKLZT150 | - | | 150 | | | 14,299 | 1 | STK |
| ZMKLZT200 | DF | 150 | 208 | | | 14,515 | 1 | STK |
| ZMKLZT300 | DF | 150 | 308 | | | 15,766 | 1 | STK |
| ZMKLZT400 | DF | 150 | 408 | | | 16,892 | 1 | STK |
| ZMKLZT500 | DF | 150 | 508 | | | 18,017 | 1 | STK |
| ZMKLZT600 | DF | 150 | 608 | | | 20,921 | 1 | STK |
| ZMKLZT800 | - | | 800 | | | 23,432 | 1 | STK |
| ZMKLZT1000 | - | | 1000 | | | 26,680 | 1 | STK |
| PEKLZT150 | - | 150 | 150 | | | 14,299 | 1 | STK |
| PEKLZT800 | - | 150 | 800 | | | 23,432 | 1 | STK |
| PEKLZT1000 | - | 150 | 1000 | | | 26,680 | 1 | STK |

Nombre minimal des boulons et des écrous: 12 pièces.

Légende de la finition

- SZ = Sendzimir
- DF = Defender