

# AS

## Aftakstuk 90°



Ineenschuifbaar met de kabelbaan

Radius: 100 mm

Op aanvraag: Hoogte 35 mm - 85 mm - 110 mm (enkel in SZ en HD)

|   |     |     |     |     |     |     |     |     |      |
|---|-----|-----|-----|-----|-----|-----|-----|-----|------|
|   | 50  | 75  | 100 | 150 | 200 | 300 | 400 | 500 | 600  |
| A | 458 | 483 | 508 | 558 | 608 | 708 | 808 | 908 | 1008 |

### Te bevestigen met:



Zelfborgende  
moer en bout  
VM



Zelfborgende  
moer en  
kraagbout  
VMK

| Artikel            | Afwerking | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Eenh. |
|--------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| <b>ZMAS110.100</b> | DF        | 110     | 100     | 0,75       |         | 0,691  | 1 | STK   |
| <b>ZMAS110.150</b> | DF        | 110     | 150     | 0,75       |         | 0,757  | 1 | STK   |
| <b>ZMAS110.200</b> | DF        | 110     | 200     | 0,75       |         | 0,821  | 1 | STK   |
| <b>ZMAS110.300</b> | DF        | 110     | 300     | 0,75       |         | 0,944  | 1 | STK   |
| <b>ZMAS110.400</b> | DF        | 110     | 400     | 0,75       |         | 1,075  | 1 | STK   |
| <b>ZMAS110.500</b> | DF        | 110     | 500     | 0,75/0,9   |         | 1,407  | 1 | STK   |
| <b>ZMAS110.600</b> | DF        | 110     | 600     | 0,75/0,9   |         | 1,576  | 1 | STK   |
| <b>ZMAS85.100</b>  | DF        | 85      | 100     | 0,75       |         | 0,600  | 1 | STK   |
| <b>ZMAS85.150</b>  | DF        | 85      | 150     | 0,75       |         | 0,666  | 1 | STK   |
| <b>ZMAS85.200</b>  | DF        | 85      | 200     | 0,75       |         | 0,730  | 1 | STK   |
| <b>ZMAS85.300</b>  | DF        | 85      | 300     | 0,75       |         | 0,853  | 1 | STK   |
| <b>ZMAS85.400</b>  | DF        | 85      | 400     | 0,75       |         | 0,984  | 1 | STK   |
| <b>ZMAS85.500</b>  | DF        | 85      | 500     | 0,75/0,9   |         | 1,316  | 1 | STK   |
| <b>ZMAS85.600</b>  | DF        | 85      | 600     | 0,75/0,9   |         | 1,486  | 1 | STK   |
| <b>ZMAS60.100</b>  | DF        | 60      | 100     |            |         | 0,512  | 1 | STK   |
| <b>ZMAS60.050</b>  | DF        | 60      | 50      |            |         | 0,446  | 1 | STK   |
| <b>ZMAS60.075</b>  | DF        | 60      | 75      |            |         | 0,479  | 1 | STK   |
| <b>ZMAS60.150</b>  | DF        | 60      | 150     |            |         | 0,578  | 1 | STK   |
| <b>ZMAS60.200</b>  | DF        | 60      | 200     |            |         | 0,642  | 1 | STK   |
| <b>ZMAS60.300</b>  | DF        | 60      | 300     |            |         | 0,765  | 1 | STK   |
| <b>ZMAS60.400</b>  | DF        | 60      | 400     |            |         | 0,896  | 1 | STK   |
| <b>ZMAS60.500</b>  | DF        | 60      | 500     |            |         | 1,228  | 1 | STK   |
| <b>ZMAS60.600</b>  | DF        | 60      | 600     |            |         | 1,398  | 1 | STK   |

Minimum aantal bouten en moeren: 8 stuks.

### Legende afwerking

- DF = Defender

