


B90

Horizontale bocht 90°

Ineenschuifbaar met de kabelbaan

Radius: 100 mm

Op aanvraag: Hoogte 35 mm - 85 mm - 110 mm (enkel in SZ en HD)




	50	75	100	150	200	300	400	500	600
A	255	280	305	355	405	505	605	705	805
B	255	280	305	355	405	505	605	705	805

Te bevestigen met:



Zelfborgende
moer en bout
VM



Zelfborgende
moer en
kraagbout
VMK

Artikel	Afwerking	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Eenh.
ZMB90.110.100	DF	110	100	0,75		0,958	1	STK
ZMB90.110.150	DF	110	150	0,75		1,211	1	STK
ZMB90.110.200	DF	110	200	0,75		1,490	1	STK
ZMB90.110.300	DF	110	300	0,75		2,132	1	STK
ZMB90.110.400	DF	110	400	0,75		2,884	1	STK
ZMB90.110.500	DF	110	500	0,75/0,9		4,461	1	STK
ZMB90.110.600	DF	110	600	0,75/0,9		5,669	1	STK
ZMB90.85.100	DF	85	100	0,75		0,833	1	STK
ZMB90.85.150	DF	85	150	0,75		1,072	1	STK
ZMB90.85.200	DF	85	200	0,75		1,338	1	STK
ZMB90.85.300	DF	85	300	0,75		1,952	1	STK
ZMB90.85.400	DF	85	400	0,75		2,677	1	STK
ZMB90.85.500	DF	85	500	0,75/0,9		4,226	1	STK
ZMB90.85.600	DF	85	600	0,75/0,9		5,407	1	STK
ZMB90.60.050	DF	85	600			0,514	1	STK
ZMB90.60.075	DF	85	500			0,609	1	STK
ZMB90.60.100	DF	60	100			0,712	1	STK
ZMB90.60.150	DF	60	150			0,937	1	STK
ZMB90.60.200	DF	60	200			1,189	1	STK
ZMB90.60.300	DF	60	300			1,777	1	STK
ZMB90.60.400	DF	60	400			2,475	1	STK
ZMB90.60.500	DF	60	500			3,997	1	STK
ZMB90.60.600	DF	60	600			5,151	1	STK

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- DF = Defender

