


# VB90

## Valbocht 90°



Ineenschuifbaar met de kabelbaan

Radius: 100 mm

Op aanvraag: Hoogte 35 mm - 85 mm - 110 mm (enkel in SZ en HD)

Artikel	Afwerking	↕ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Eenh.
<b>ZMVB90.110.100</b>	DF	110	100	0,75		0,813	1	STK
<b>ZMVB90.110.150</b>	DF	110	150	0,75		0,912	1	STK
<b>ZMVB90.110.200</b>	DF	110	200	0,75		1,010	1	STK
<b>ZMVB90.110.300</b>	DF	110	300	0,75		1,208	1	STK
<b>ZMVB90.110.400</b>	DF	110	400	0,75		1,405	1	STK
<b>ZMVB90.110.500</b>	DF	110	500	0,75/0,9		1,885	1	STK
<b>ZMVB90.110.600</b>	DF	110	600	0,75/0,9		2,139	1	STK
<b>ZMVB90.85.100</b>	DF	85	100	0,75		0,675	1	STK
<b>ZMVB90.85.150</b>	DF	85	150	0,75		0,774	1	STK
<b>ZMVB90.85.200</b>	DF	85	200	0,75		0,872	1	STK
<b>ZMVB90.85.300</b>	DF	85	300	0,75		1,070	1	STK
<b>ZMVB90.85.400</b>	DF	85	400	0,75		1,267	1	STK
<b>ZMVB90.85.500</b>	DF	85	500	0,75/0,9		1,747	1	STK
<b>ZMVB90.85.600</b>	DF	85	600	0,75/0,9		2,001	1	STK
<b>ZMVB90.60.050</b>	DF	60	50			0,449	1	STK
<b>ZMVB90.60.075</b>	DF	60	75			0,498	1	STK
<b>ZMVB90.60.100</b>	DF	60	100			0,548	1	STK
<b>ZMVB90.60.150</b>	DF	60	150			0,646	1	STK
<b>ZMVB90.60.200</b>	DF	60	200			0,745	1	STK
<b>ZMVB90.60.300</b>	DF	60	300			0,942	1	STK
<b>ZMVB90.60.400</b>	DF	60	400			1,140	1	STK
<b>ZMVB90.60.500</b>	DF	60	501,4	0,9		1,430	1	STK
<b>ZMVB90.60.600</b>	DF	60	601,4	0,9		1,600	1	STK

### Te bevestigen met:



Zelfborgende  
moer en bout  
VM



Zelfborgende  
moer en  
kraagbout  
VMK

Minimum aantal bouten en moeren: 8 stuks.

### Legende afwerking

- DF = Defender