


# KLLT

## T-stuk voor KLL



Radius: 300 mm

|   |      |      |      |      |      |      |
|---|------|------|------|------|------|------|
|   | 150  | 200  | 300  | 400  | 500  | 600  |
| A | 1021 | 1071 | 1171 | 1271 | 1371 | 1471 |

**Te bevestigen met:**



Zelfborgende moer en bout  
VM

| Artikel              | Afwerking | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Eenh. |
|----------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| <b>KLLT60.150</b>    | -         | 60      | 141     |            |         | 2,229  | 1 | STK   |
| <b>KLLT60.200</b>    | -         | 60      | 191     |            |         | 2,821  | 1 | STK   |
| <b>KLLT60.300</b>    | -         | 60      | 291     |            |         | 3,447  | 1 | STK   |
| <b>KLLT60.400</b>    | -         | 60      | 391     |            |         | 3,882  | 1 | STK   |
| <b>KLLT60.450</b>    | -         | 60      | 443     |            |         | 4,099  | 1 | STK   |
| <b>KLLT60.500</b>    | -         | 60      | 491     |            |         | 4,317  | 1 | STK   |
| <b>KLLT60.600</b>    | -         | 60      | 591     |            |         | 4,753  | 1 | STK   |
| <b>KLLT60.750</b>    | SZ        | 60      | 750     | 1,25       |         | 7,554  | 1 | STK   |
| <b>KLLT60.800</b>    | SZ        | 60      | 800     | 1,25       |         | 7,896  | 1 | STK   |
| <b>KLLT60.900</b>    | SZ        | 60      | 900     | 1,25       |         | 8,580  | 1 | STK   |
| <b>KLLT110.150</b>   | -         | 110     | 145     |            |         | 3,635  | 1 | STK   |
| <b>KLLT110.200</b>   | -         | 110     | 195     |            |         | 4,131  | 1 | STK   |
| <b>KLLT110.300</b>   | -         | 110     | 295     |            |         | 4,806  | 1 | STK   |
| <b>KLLT110.400</b>   | -         | 110     | 395     |            |         | 5,290  | 1 | STK   |
| <b>KLLT110.450</b>   | -         | 110     | 445     |            |         | 5,533  | 1 | STK   |
| <b>KLLT110.500</b>   | -         | 110     | 495     |            |         | 5,775  | 1 | STK   |
| <b>KLLT110.600</b>   | -         | 110     | 595     |            |         | 6,260  | 1 | STK   |
| <b>KLLT110.750</b>   | -         | 110     | 750     |            |         | 6,987  | 1 | STK   |
| <b>KLLT110.800</b>   | SZ        | 110     | 800     | 1,25       |         | 9,478  | 1 | STK   |
| <b>KLLT110.900</b>   | -         | 110     | 900     |            |         | 7,714  | 1 | STK   |
| <b>ZMKLLT60.150</b>  | DF        | 60      | 150     | 1,25       |         | 3,229  | 1 | STK   |
| <b>ZMKLLT60.200</b>  | DF        | 60      | 200     | 1,25       |         | 3,483  | 1 | STK   |
| <b>ZMKLLT60.300</b>  | DF        | 60      | 300     | 1,25       |         | 4,154  | 1 | STK   |
| <b>ZMKLLT60.400</b>  | DF        | 60      | 400     | 1,25       |         | 4,721  | 1 | STK   |
| <b>ZMKLLT60.450</b>  | DF        | 60      | 450     | 1,25       |         | 5,005  | 1 | STK   |
| <b>ZMKLLT60.500</b>  | DF        | 60      | 500     | 1,25       |         | 5,566  | 1 | STK   |
| <b>ZMKLLT60.600</b>  | DF        | 60      | 600     | 1,25       |         | 6,193  | 1 | STK   |
| <b>ZMKLLT60.750</b>  | DF        | 60      | 750     | 1,25       |         | 7,554  | 1 | STK   |
| <b>ZMKLLT60.800</b>  | DF        | 60      | 800     | 1,25       |         | 7,896  | 1 | STK   |
| <b>ZMKLLT60.900</b>  | DF        | 60      | 900     | 1,25       |         | 8,580  | 1 | STK   |
| <b>ZMKLLT110.150</b> | DF        | 110     | 150     | 1,25       |         | 4,493  | 1 | STK   |
| <b>ZMKLLT110.200</b> | DF        | 110     | 200     | 1,25       |         | 4,772  | 1 | STK   |
| <b>ZMKLLT110.300</b> | DF        | 110     | 300     | 1,25       |         | 5,491  | 1 | STK   |
| <b>ZMKLLT110.400</b> | DF        | 110     | 400     | 1,25       |         | 6,107  | 1 | STK   |
| <b>ZMKLLT110.450</b> | DF        | 110     | 450     | 1,25       |         | 6,416  | 1 | STK   |
| <b>ZMKLLT110.500</b> | DF        | 110     | 500     | 1,25       |         | 7,001  | 1 | STK   |
| <b>ZMKLLT110.600</b> | DF        | 110     | 600     | 1,25       |         | 7,677  | 1 | STK   |
| <b>ZMKLLT110.750</b> | DF        | 110     | 750     | 1,25       |         | 9,111  | 1 | STK   |
| <b>ZMKLLT110.800</b> | DF        | 110     | 800     | 1,25       |         | 9,478  | 1 | STK   |
| <b>ZMKLLT110.900</b> | DF        | 110     | 900     | 1,25       |         | 10,210 | 1 | STK   |

Minimum aantal bouten en moeren VM6.10: 12 stuks.

**Legende afwerking**

- SZ = Sendzimir
- DF = Defender