

KLM100SB45

Stijgbocht 45° voor KLM100



Radius: 600 mm

| Artikel | Afwerking | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|--------------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| KLM100SB45.150 | SZ | 100 | 158 | | | 2,724 | 1 | STK |
| KLM100SB45.200 | SZ | 100 | 208 | | | 2,840 | 1 | STK |
| KLM100SB45.300 | SZ | 100 | 308 | | | 3,070 | 1 | STK |
| KLM100SB45.400 | SZ | 100 | 408 | | | 3,300 | 1 | STK |
| KLM100SB45.450 | SZ | 100 | 458 | | | 3,416 | 1 | STK |
| KLM100SB45.500 | SZ | 100 | 508 | | | 3,531 | 1 | STK |
| KLM100SB45.600 | SZ | 100 | 608 | | | 3,761 | 1 | STK |
| KLM100SB45.750 | SZ | 100 | 758 | | | 4,107 | 1 | STK |
| KLM100SB45.800 | SZ | 100 | 808 | | | 4,222 | 1 | STK |
| KLM100SB45.900 | SZ | 100 | 908 | | | 4,453 | 1 | STK |
| KLM100SB45.1000 | SZ | 100 | 1008 | | | 4,683 | 1 | STK |
| ZMKLM100SB45.150 | DF | 100 | 158 | | | 2,724 | 1 | STK |
| ZMKLM100SB45.200 | DF | 100 | 208 | | | 2,840 | 1 | STK |
| ZMKLM100SB45.300 | DF | 100 | 308 | | | 3,070 | 1 | STK |
| ZMKLM100SB45.400 | DF | 100 | 408 | | | 3,300 | 1 | STK |
| ZMKLM100SB45.450 | DF | 100 | 458 | | | 3,416 | 1 | STK |
| ZMKLM100SB45.500 | DF | 100 | 508 | | | 3,531 | 1 | STK |
| ZMKLM100SB45.600 | DF | 100 | 608 | | | 3,761 | 1 | STK |
| ZMKLM100SB45.750 | DF | 100 | 758 | | | 4,107 | 1 | STK |
| ZMKLM100SB45.800 | DF | 100 | 808 | | | 4,222 | 1 | STK |
| ZMKLM100SB45.900 | DF | 100 | 908 | | | 4,453 | 1 | STK |
| ZMKLM100SB45.1000 | DF | 100 | 1008 | | | 4,683 | 1 | STK |

Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK



Zelfborgende
flensmoer (DIN
6923)
RM

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender