

KLM125B45

Horizontale bocht voor KLM125



Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK

Zelfborgende
flensmoer (DIN
6923)
RM

Radius: 600 mm

| Artikel | Afwerking | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|-------------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| KLM125B45.150 | SZ | 125 | 158 | | | 4,084 | 1 | STK |
| KLM125B45.200 | SZ | 125 | 208 | | | 4,312 | 1 | STK |
| KLM125B45.300 | SZ | 125 | 308 | | | 4,767 | 1 | STK |
| KLM125B45.400 | SZ | 125 | 408 | | | 5,223 | 1 | STK |
| KLM125B45.450 | SZ | 125 | 458 | | | 5,451 | 1 | STK |
| KLM125B45.500 | SZ | 125 | 508 | | | 6,035 | 1 | STK |
| KLM125B45.600 | SZ | 125 | 608 | | | 6,567 | 1 | STK |
| KLM125B45.750 | SZ | 125 | 758 | | | 7,366 | 1 | STK |
| KLM125B45.800 | SZ | 125 | 808 | | | 7,632 | 1 | STK |
| KLM125B45.900 | SZ | 125 | 908 | | | 8,165 | 1 | STK |
| KLM125B45.1000 | SZ | 125 | 1008 | | | 9,438 | 1 | STK |
| ZMKLM125B45.150 | DF | 125 | 158 | | | 4,084 | 1 | STK |
| ZMKLM125B45.200 | DF | 125 | 208 | | | 4,312 | 1 | STK |
| ZMKLM125B45.300 | DF | 125 | 308 | | | 4,767 | 1 | STK |
| ZMKLM125B45.400 | DF | 125 | 408 | | | 5,223 | 1 | STK |
| ZMKLM125B45.450 | DF | 125 | 458 | | | 5,451 | 1 | STK |
| ZMKLM125B45.500 | DF | 125 | 508 | | | 6,035 | 1 | STK |
| ZMKLM125B45.600 | DF | 125 | 608 | | | 6,567 | 1 | STK |
| ZMKLM125B45.750 | DF | 125 | 758 | | | 7,366 | 1 | STK |
| ZMKLM125B45.800 | DF | 125 | 808 | | | 7,632 | 1 | STK |
| ZMKLM125B45.900 | DF | 125 | 908 | | | 8,165 | 1 | STK |
| ZMKLM125B45.1000 | DF | 125 | 1008 | | | 9,438 | 1 | STK |

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender