

KLM125B45

Horizontale bocht voor KLM125



Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK

Zelfborgende
flensmoer (DIN
6923)
RM

Radius: 600 mm

Artikel	Afwerking	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Eenh.
KLM125B45.150	SZ	125	158			4,084	1	STK
KLM125B45.200	SZ	125	208			4,312	1	STK
KLM125B45.300	SZ	125	308			4,767	1	STK
KLM125B45.400	SZ	125	408			5,223	1	STK
KLM125B45.450	SZ	125	458			5,451	1	STK
KLM125B45.500	SZ	125	508			6,035	1	STK
KLM125B45.600	SZ	125	608			6,567	1	STK
KLM125B45.750	SZ	125	758			7,366	1	STK
KLM125B45.800	SZ	125	808			7,632	1	STK
KLM125B45.900	SZ	125	908			8,165	1	STK
KLM125B45.1000	SZ	125	1008			9,438	1	STK
ZMKLM125B45.150	DF	125	158			4,084	1	STK
ZMKLM125B45.200	DF	125	208			4,312	1	STK
ZMKLM125B45.300	DF	125	308			4,767	1	STK
ZMKLM125B45.400	DF	125	408			5,223	1	STK
ZMKLM125B45.450	DF	125	458			5,451	1	STK
ZMKLM125B45.500	DF	125	508			6,035	1	STK
ZMKLM125B45.600	DF	125	608			6,567	1	STK
ZMKLM125B45.750	DF	125	758			7,366	1	STK
ZMKLM125B45.800	DF	125	808			7,632	1	STK
ZMKLM125B45.900	DF	125	908			8,165	1	STK
ZMKLM125B45.1000	DF	125	1008			9,438	1	STK

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender