


KLM125SB

Stijgbocht voor KLM125



Radius: 600 mm

| Artikel | Afwerking | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|-----------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| KLM125SB150 | SZ | 125 | 158 | | | 5,061 | 1 | STK |
| KLM125SB200 | SZ | 125 | 208 | | | 5,215 | 1 | STK |
| KLM125SB300 | SZ | 125 | 308 | | | 5,522 | 1 | STK |
| KLM125SB400 | SZ | 125 | 408 | | | 5,829 | 1 | STK |
| KLM125SB450 | SZ | 125 | 458 | | | 5,983 | 1 | STK |
| KLM125SB500 | SZ | 125 | 508 | | | 6,136 | 1 | STK |
| KLM125SB600 | SZ | 125 | 608 | | | 6,443 | 1 | STK |
| KLM125SB750 | SZ | 125 | 758 | | | 6,904 | 1 | STK |
| KLM125SB800 | SZ | 125 | 808 | | | 7,058 | 1 | STK |
| KLM125SB900 | SZ | 125 | 908 | | | 7,365 | 1 | STK |
| KLM125SB1000 | SZ | 125 | 1008 | | | 7,672 | 1 | STK |
| ZMKLM125SB150 | DF | 125 | 158 | | | 5,061 | 1 | STK |
| ZMKLM125SB200 | DF | 125 | 208 | | | 5,215 | 1 | STK |
| ZMKLM125SB300 | DF | 125 | 308 | | | 5,522 | 1 | STK |
| ZMKLM125SB400 | DF | 125 | 408 | | | 5,829 | 1 | STK |
| ZMKLM125SB450 | DF | 125 | 458 | | | 5,983 | 1 | STK |
| ZMKLM125SB500 | DF | 125 | 508 | | | 6,136 | 1 | STK |
| ZMKLM125SB600 | DF | 125 | 608 | | | 6,443 | 1 | STK |
| ZMKLM125SB750 | DF | 125 | 758 | | | 6,904 | 1 | STK |
| ZMKLM125SB800 | DF | 125 | 808 | | | 7,058 | 1 | STK |
| ZMKLM125SB900 | DF | 125 | 908 | | | 7,365 | 1 | STK |
| ZMKLM125SB1000 | DF | 125 | 1008 | | | 7,672 | 1 | STK |

Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK

Zelfborgende
flensmoer (DIN
6923)
RM

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender