


KLM125VB

Valbocht voor KLM125



Te bevestigen met:



Zelfborgende
flensmoer (DIN
6923)
RM



Zelfborgende
kraagbout (DIN
603)
RBK

Radius: 600 mm

| Artikel | Afwerking | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|-----------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| KLM125VB150 | SZ | 125 | 158 | | | 4,974 | 1 | STK |
| KLM125VB200 | SZ | 125 | 208 | | | 5,089 | 1 | STK |
| KLM125VB300 | SZ | 125 | 308 | | | 5,320 | 1 | STK |
| KLM125VB400 | SZ | 125 | 408 | | | 5,550 | 1 | STK |
| KLM125VB450 | SZ | 125 | 458 | | | 5,666 | 1 | STK |
| KLM125VB500 | SZ | 125 | 508 | | | 5,781 | 1 | STK |
| KLM125VB600 | SZ | 125 | 608 | | | 6,011 | 1 | STK |
| KLM125VB750 | SZ | 125 | 758 | | | 6,357 | 1 | STK |
| KLM125VB800 | SZ | 125 | 808 | | | 6,472 | 1 | STK |
| KLM125VB900 | SZ | 125 | 908 | | | 6,702 | 1 | STK |
| KLM125VB1000 | SZ | 125 | 1008 | | | 6,933 | 1 | STK |
| ZMKLM125VB150 | DF | 125 | 158 | | | 4,974 | 1 | STK |
| ZMKLM125VB200 | DF | 125 | 208 | | | 5,089 | 1 | STK |
| ZMKLM125VB300 | DF | 125 | 308 | | | 5,320 | 1 | STK |
| ZMKLM125VB400 | DF | 125 | 408 | | | 5,550 | 1 | STK |
| ZMKLM125VB450 | DF | 125 | 458 | | | 5,666 | 1 | STK |
| ZMKLM125VB500 | DF | 125 | 508 | | | 5,781 | 1 | STK |
| ZMKLM125VB600 | DF | 125 | 608 | | | 6,011 | 1 | STK |
| ZMKLM125VB750 | DF | 125 | 758 | | | 6,357 | 1 | STK |
| ZMKLM125VB800 | DF | 125 | 808 | | | 6,472 | 1 | STK |
| ZMKLM125VB900 | DF | 125 | 908 | | | 6,702 | 1 | STK |
| ZMKLM125VB1000 | DF | 125 | 1008 | | | 6,933 | 1 | STK |

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender