


KLM125VB45

Valbocht voor KLM125



Radius: 600 mm

| Artikel | Afwerking | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|--------------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| KLM125VB45.150 | SZ | 125 | 158 | | | 3,200 | 1 | STK |
| KLM125VB45.200 | SZ | 125 | 208 | | | 3,276 | 1 | STK |
| KLM125VB45.300 | SZ | 125 | 308 | | | 3,430 | 1 | STK |
| KLM125VB45.400 | SZ | 125 | 408 | | | 3,584 | 1 | STK |
| KLM125VB45.450 | SZ | 125 | 458 | | | 3,660 | 1 | STK |
| KLM125VB45.500 | SZ | 125 | 508 | | | 3,737 | 1 | STK |
| KLM125VB45.600 | SZ | 125 | 608 | | | 3,891 | 1 | STK |
| KLM125VB45.750 | SZ | 125 | 758 | | | 4,121 | 1 | STK |
| KLM125VB45.800 | SZ | 125 | 808 | | | 4,198 | 1 | STK |
| KLM125VB45.900 | SZ | 125 | 908 | | | 4,352 | 1 | STK |
| KLM125VB45.1000 | SZ | 125 | 1008 | | | 4,505 | 1 | STK |
| ZMKLM125VB45.150 | DF | 125 | 158 | | | 3,200 | 1 | STK |
| ZMKLM125VB45.200 | DF | 125 | 208 | | | 3,276 | 1 | STK |
| ZMKLM125VB45.300 | DF | 125 | 308 | | | 3,430 | 1 | STK |
| ZMKLM125VB45.400 | DF | 125 | 408 | | | 3,584 | 1 | STK |
| ZMKLM125VB45.450 | DF | 125 | 458 | | | 3,660 | 1 | STK |
| ZMKLM125VB45.500 | DF | 125 | 508 | | | 3,737 | 1 | STK |
| ZMKLM125VB45.600 | DF | 125 | 608 | | | 3,891 | 1 | STK |
| ZMKLM125VB45.750 | DF | 125 | 758 | | | 4,121 | 1 | STK |
| ZMKLM125VB45.800 | DF | 125 | 808 | | | 4,198 | 1 | STK |
| ZMKLM125VB45.900 | DF | 125 | 908 | | | 4,352 | 1 | STK |
| ZMKLM125VB45.1000 | DF | 125 | 1008 | | | 4,505 | 1 | STK |

Te bevestigen met:



Zelfborgende
flensmoer (DIN
6923)
RM

Zelfborgende
kraagbout (DIN
603)
RBK

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender