

KLWVSB

Val- en stijgbocht voor KLW



Schuift in de C-opening van de langsligger.
Voorgemonteerd.

Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK

Zelfborgende
flensmoer (DIN
6923)
RM

| Artikel | Afwerking | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|--------------------|-----------|---------|---------|--------------|---------|--------|---|-------|
| KLWVSB200 | - | 200 | 218 | | 1175 | 19,060 | 1 | STK |
| KLWVSB300 | - | 200 | 318 | | 1175 | 19,380 | 1 | STK |
| KLWVSB400 | - | 200 | 418 | | 1175 | 19,700 | 1 | STK |
| KLWVSB500 | - | 200 | 518 | | 1175 | 20,020 | 1 | STK |
| KLWVSB600 | - | 200 | 618 | | 1175 | 20,350 | 1 | STK |
| HDKLWVSB200 | HD | 200 | 200 | 2,0/1,25/3,0 | 1175 | 19,060 | 1 | STK |
| HDKLWVSB300 | HD | 200 | 300 | 2,0/1,25/3,0 | 1175 | 19,380 | 1 | STK |
| HDKLWVSB400 | HD | 200 | 400 | 2,0/1,25/3,0 | 1175 | 19,700 | 1 | STK |
| HDKLWVSB500 | HD | 200 | 500 | 2,0/1,25/3,0 | 1175 | 20,020 | 1 | STK |
| HDKLWVSB600 | HD | 200 | 600 | 2,0/1,25/3,0 | 1175 | 20,350 | 1 | STK |

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- HD =