

ZMDIG

Deksel industrieel



Te bevestigen met:



Dekselklem
ZMDKIG

| Artikel | Afwerking | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/m | 📦 | Eenh. |
|------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| ZMDIG150 | DF | 15 | 173 | | 2000 | 1,427 | 2 | M |
| ZMDIG200 | DF | 15 | 223 | | 2000 | 1,780 | 2 | M |
| ZMDIG300 | DF | 15 | 323 | | 2000 | 2,487 | 2 | M |
| ZMDIG400 | DF | 15 | 423 | | 2000 | 3,193 | 2 | M |
| ZMDIG450 | DF | 15 | 473 | | 2000 | 3,547 | 2 | M |
| ZMDIG500 | DF | 15 | 523 | | 2000 | 3,900 | 2 | M |
| ZMDIG600 | DF | 15 | 623 | | 2000 | 4,606 | 2 | M |
| ZMDIG750 | DF | 15 | 773 | | 2000 | 7,861 | 2 | M |
| ZMDIG800 | DF | 15 | 823 | | 2000 | 8,352 | 2 | M |
| ZMDIG900 | DF | 15 | 923 | | 2000 | 9,333 | 2 | M |
| ZMDIG1000 | DF | 15 | 1023 | | 2000 | 10,314 | 2 | M |

Deksels met breedtemaat > of = 400 mm worden geleverd met diagonale versterkingsribben.

Legende afwerking

- DF = Defender