

KLZB

Horizontale bocht voor KLZ



Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK

Zelfborgende
flensmoer (DIN
6923)
RM

Radius: 600 mm

| Artikel | Afwerking | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|-------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| KLZB150 | - | 150 | 150 | | | 7,241 | 1 | STK |
| KLZB200 | SZ | 150 | 208 | | | 7,639 | 1 | STK |
| KLZB300 | SZ | 150 | 308 | | | 8,520 | 1 | STK |
| KLZB400 | SZ | 150 | 408 | | | 9,400 | 1 | STK |
| KLZB500 | SZ | 150 | 508 | | | 10,281 | 1 | STK |
| KLZB600 | SZ | 150 | 608 | | | 11,162 | 1 | STK |
| KLZB800 | - | 150 | 800 | | | 14,141 | 1 | STK |
| KLZB1000 | - | 150 | 1000 | | | 16,052 | 1 | STK |
| ZMKLZB150 | - | | 150 | | | 7,241 | 1 | STK |
| ZMKLZB200 | DF | 150 | 208 | | | 7,639 | 1 | STK |
| ZMKLZB300 | DF | 150 | 308 | | | 8,520 | 1 | STK |
| ZMKLZB400 | DF | 150 | 408 | | | 9,400 | 1 | STK |
| ZMKLZB500 | DF | 150 | 508 | | | 10,281 | 1 | STK |
| ZMKLZB600 | DF | 150 | 608 | | | 11,162 | 1 | STK |
| ZMKLZB800 | - | | 800 | | | 14,141 | 1 | STK |
| ZMKLZB1000 | - | | 1000 | | | 16,052 | 1 | STK |
| PEKLZB150 | - | 150 | 150 | | | 7,241 | 1 | STK |
| PEKLZB800 | - | 150 | 800 | | | 14,141 | 1 | STK |
| PEKLZB1000 | - | 150 | 1000 | | | 16,052 | 1 | STK |

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender