


P1000T

Montageprofiel



| Artikel | Afwerking | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/m | 📦 | Eenh. |
|--------------------|-----------|---------|---------|------------|---------|-------|---|-------|
| P1000TP | PO | 41 | 41 | 2,5 | 6000 | 2,605 | 6 | M |
| P1000T | PG | 41 | 41 | 2,5 | 6000 | 2,647 | 6 | M |
| P1000TDF | DF | 41 | 41 | 2,5 | 6000 | 2,647 | 6 | M |
| P1000TPX3 | PO | 41 | 41 | 2,5 | 3000 | 2,605 | 3 | M |
| P1000TX3 | ZP | 41 | 41 | 2,5 | 3000 | 2,730 | 3 | M |
| P1000TX3DF | DF | 41 | 41 | 2,5 | 3000 | 2,647 | 3 | M |
| P1000TX2000 | ZP | 41 | 41 | 2,5 | 3000 | 2,462 | 2 | M |
| P1000THX2 | HG | 41 | 41 | 2,5 | 2000 | 2,730 | 2 | M |

T = 28x14mm

Afkorting:

- PO = Onbehandeld
- ZP = Verzinkt
- HG = Hot-dip Gegalvaniseerd
- DF = Defender

Legende afwerking

- PO = Onbehandeld
- PG = Voorverzinkt
- DF = Defender
- ZP = Elektrolytisch verzinkt
- HG = Thermisch verzinkt