


I6KLLX  
Kruisstuk voor I6KLL



Radius: 300 mm


Stand. Uitv.

Inox 316

|   | 150  | 200  | 300  | 400  | 500  | 600  |
|---|------|------|------|------|------|------|
| A | 1021 | 1071 | 1171 | 1271 | 1371 | 1471 |

| HD | Artikel      | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Stock | Eenh. |
|----|--------------|---------|---------|------------|---------|--------|---|-------|-------|
| -  | I6KLLX60.150 | 60      | 141     |            |         | 3,131  | 1 |       | STK   |
| -  | I6KLLX60.200 | 60      | 191     |            |         | 3,232  | 1 |       | STK   |
| -  | I6KLLX60.300 | 60      | 291     |            |         | 4,421  | 1 |       | STK   |
| -  | I6KLLX60.400 | 60      | 391     |            |         | 4,875  | 1 |       | STK   |
| -  | I6KLLX60.500 | 60      | 491     |            |         | 5,329  | 1 |       | STK   |
| -  | I6KLLX60.600 | 60      | 591     |            |         | 5,782  | 1 |       | STK   |

Te bevestigen met:



Minimum aantal bouten en moeren: 16 stuks.

Gebeitst en gepassiveerd.

Zelfborgende moer en bout  
I6VM