

I6KLM100SB

Stijgbocht voor I6KLM100



Radius: 600 mm

| Artikel | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|-----------------------|---------|---------|------------|---------|--------|---|-------|
| I6KLM100SB150 | 100 | 150 | | | 4,315 | 1 | STK |
| I6KLM100SB200 | 100 | 208 | | | 4,471 | 1 | STK |
| I6KLM100SB300 | 100 | 308 | | | 4,787 | 1 | STK |
| I6KLM100SB400 | 100 | 408 | | | 5,102 | 1 | STK |
| I6KLM100SB450 | 100 | 450 | | | 5,260 | 1 | STK |
| I6KLM100SB500 | 100 | 508 | | | 5,417 | 1 | STK |
| I6KLM100SB600 | 100 | 608 | | | 5,732 | 1 | STK |
| I6KLM100SB750 | 100 | 750 | | | 6,204 | 1 | STK |
| I6KLM100SB800 | 100 | 800 | | | 6,362 | 1 | STK |
| I6KLM100SB900 | 100 | 900 | | | 6,677 | 1 | STK |
| I6KLM100SB1000 | 100 | 1000 | | | 6,992 | 1 | STK |

Te bevestigen met:



Zelfborgende
kraagbout
I6RBK

Sluitring (DIN
125-1 A)
I6RO



Moer (DIN 934)
I6M

Minimum aantal bouten en moeren: 8 stuks.

Gebeitst en gepassiveerd.