

# I6KLM125B

## Horizontale bocht voor I6KLM125



### Te bevestigen met:



Zelfborgende  
kraagbout  
I6RBK

Moer (DIN 934)  
I6M



Sluitring (DIN  
125-1 A)  
I6RO

Radius: 600 mm

Artikel	↕ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Eenh.
<b>I6KLM125B150</b>	125	150			6,456	1	STK
<b>I6KLM125B200</b>	125	208			6,884	1	STK
<b>I6KLM125B300</b>	125	308			7,739	1	STK
<b>I6KLM125B400</b>	125	408			8,595	1	STK
<b>I6KLM125B450</b>	125	450			9,023	1	STK
<b>I6KLM125B500</b>	125	508			9,450	1	STK
<b>I6KLM125B600</b>	125	608			10,306	1	STK
<b>I6KLM125B750</b>	125	750			12,714	1	STK
<b>I6KLM125B800</b>	125	800			13,220	1	STK
<b>I6KLM125B900</b>	125	900			14,234	1	STK
<b>I6KLM125B1000</b>	125	1000			18,323	1	STK

Minimum aantal bouten en moeren: 8 stuks.

Gebeitst en gepassiveerd.