

# I6KLM125T

## T-stuk voor I6KLM125



Radius: 600 mm

	200	300	400	500	600
A	1962	2062	2162	2262	2362

### Te bevestigen met:



Zelfborgende  
kraagbout  
I6RBK

Moer (DIN 934)  
I6M

Artikel	↕ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Eenh.
<b>I6KLM125T150</b>	125	150			13,373	1	STK
<b>I6KLM125T200</b>	125	208			13,945	1	STK
<b>I6KLM125T300</b>	125	308			15,089	1	STK
<b>I6KLM125T400</b>	125	408			16,208	1	STK
<b>I6KLM125T450</b>	125	450			16,774	1	STK
<b>I6KLM125T500</b>	125	508			17,340	1	STK
<b>I6KLM125T600</b>	125	608			19,316	1	STK
<b>I6KLM125T750</b>	125	750			21,156	1	STK
<b>I6KLM125T800</b>	125	800			21,769	1	STK
<b>I6KLM125T900</b>	125	900			23,655	1	STK
<b>I6KLM125T1000</b>	125	1000			24,958	1	STK

Minimum aantal bouten en moeren: 12 stuks.

Gebeitst en gepassiveerd.



Sluitring (DIN  
125-1 A)  
I6RO