


VB90

Valbocht 90°



Ineenschuifbaar met de kabelbaan

Radius: 100 mm


Op aanvraag: Hoogte 35 mm - 85 mm - 110 mm (enkel in SZ en HD)

Artikel	Afwerking	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Eenh.
VB90.60.050	SZ	60	50			0,550	1	STK
VB90.60.075	SZ	60	75			0,630	1	STK
VB90.60.100	SZ	60	100			0,650	1	STK
VB90.60.150	SZ	60	150			0,780	1	STK
VB90.60.200	SZ	60	200			0,850	1	STK
VB90.60.300	SZ	60	300			1,080	1	STK
VB90.60.400	SZ	60	400			1,330	1	STK
VB90.60.500	SZ	60	500			1,430	1	STK
VB90.60.600	SZ	60	600			1,600	1	STK
ZMVB90.60.050	DF	60	50			0,55	1	STK
ZMVB90.60.075	DF	60	75			0,63	1	STK
ZMVB90.60.100	DF	60	100			0,65	1	STK
ZMVB90.60.150	DF	60	150			0,78	1	STK
ZMVB90.60.200	DF	60	200			0,85	1	STK
ZMVB90.60.300	DF	60	300			1,08	1	STK
ZMVB90.60.400	DF	60	400			1,33	1	STK
ZMVB90.60.500	DF	60	500			1,43	1	STK
ZMVB90.60.600	DF	60	600			1,6	1	STK

Te bevestigen met:



Zelfborgende
moer en bout
VM



Zelfborgende
moer en
kraagbout
VMK

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender