

KLLB

Horizontale bocht voor KLL



Te bevestigen met:



Zelfborgende moer en bout
VM

Radius: 300 mm

Artikel	Afwerking	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Eenh.
ZMKLLB60.150	DF	60	150	1,25		1,516	1	STK
ZMKLLB60.200	DF	60	200	1,25		1,695	1	STK
ZMKLLB60.300	DF	60	300	1,25		2,051	1	STK
ZMKLLB60.400	DF	60	400	1,25		3,067	1	STK
ZMKLLB60.450	DF	60	450	1,25		3,333	1	STK
ZMKLLB60.500	DF	60	500	1,25		3,598	1	STK
ZMKLLB60.600	DF	60	600	1,25		4,129	1	STK
ZMKLLB60.750	DF	60	750	1,25		4,926	1	STK
ZMKLLB60.800	DF	60	800	1,25		5,191	1	STK
ZMKLLB60.900	DF	60	900	1,25		5,722	1	STK
ZMKLLB110.150	DF	110	150	1,25		2,370	1	STK
ZMKLLB110.200	DF	110	200	1,25		2,586	1	STK
ZMKLLB110.300	DF	110	300	1,25		3,020	1	STK
ZMKLLB110.400	DF	110	400	1,25		4,112	1	STK
ZMKLLB110.450	DF	110	450	1,25		4,416	1	STK
ZMKLLB110.500	DF	110	500	1,25		4,720	1	STK
ZMKLLB110.600	DF	110	600	1,25		5,328	1	STK
ZMKLLB110.750	DF	110	750	1,25		6,239	1	STK
ZMKLLB110.800	DF	110	800	1,25		6,543	1	STK
ZMKLLB110.900	DF	110	900	1,25		7,151	1	STK
KLLB60.150	-	60	141			1,659	1	STK
KLLB60.200	-	60	191			1,898	1	STK
KLLB60.300	-	60	291			2,375	1	STK
KLLB60.400	-	60	391			2,852	1	STK
KLLB60.450	-	60	443			3,091	1	STK
KLLB60.500	-	60	491			3,329	1	STK
KLLB60.600	-	60	591			3,806	1	STK
KLLB60.750	SZ	60	750	1,25		4,926	1	STK
KLLB60.800	SZ	60	800	1,25		5,191	1	STK
KLLB60.900	SZ	60	900	1,25		5,722	1	STK
KLLB110.150	-	110	145			3,065	1	STK
KLLB110.200	-	110	195			2,826	1	STK
KLLB110.300	-	110	295			3,384	1	STK
KLLB110.400	-	110	395			3,940	1	STK
KLLB110.450	-	110	445			4,219	1	STK
KLLB110.500	-	110	495			4,498	1	STK
KLLB110.600	-	110	595			5,055	1	STK
KLLB110.750	-	110	750			5,891	1	STK
KLLB110.800	SZ	110	800	1,25		6,543	1	STK
KLLB110.900	-	110	900			6,727	1	STK

Minimum aantal bouten en moeren VM6.10: 8 stuks.

Legende afwerking

- DF = Defender
- SZ = Sendzimir