

KLZVB

Valbocht voor KLZ



Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK

Zelfborgende
flensmoer (DIN
6923)
RM

Radius: 600 mm

| Artikel | Afwerking | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|--------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| KLZVB150 | - | 150 | 150 | | | 5,856 | 1 | STK |
| KLZVB200 | SZ | 150 | 208 | | | 5,971 | 1 | STK |
| KLZVB300 | SZ | 150 | 308 | | | 6,202 | 1 | STK |
| KLZVB400 | SZ | 150 | 408 | | | 6,432 | 1 | STK |
| KLZVB600 | SZ | 150 | 608 | | | 6,893 | 1 | STK |
| KLZVB800 | - | 150 | 800 | | | 7,354 | 1 | STK |
| KLZVB1000 | - | 150 | 1000 | | | 7,815 | 1 | STK |
| ZMKLZVB150 | - | | 150 | | | 5,856 | 1 | STK |
| ZMKLZVB200 | DF | 150 | 208 | | | 5,971 | 1 | STK |
| ZMKLZVB300 | DF | 150 | 308 | | | 6,202 | 1 | STK |
| ZMKLZVB400 | DF | 150 | 408 | | | 6,432 | 1 | STK |
| ZMKLZVB500 | DF | 150 | 508 | | | 6,663 | 1 | STK |
| ZMKLZVB600 | DF | 150 | 608 | | | 6,893 | 1 | STK |
| ZMKLZVB800 | - | | 800 | | | 7,354 | 1 | STK |
| ZMKLZVB1000 | - | | 1000 | | | 7,815 | 1 | STK |
| PEKLZVB150 | - | 150 | 150 | | | 5,856 | 1 | STK |
| PEKLZVB800 | - | 150 | 800 | | | 7,354 | 1 | STK |
| PEKLZVB1000 | - | 150 | 1000 | | | 7,815 | 1 | STK |

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender