

KLZVSB

Val- en stijgbocht voor KLZ



Schuift in de C-opening van de langsligger.
Voorgemonteerd.

Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK

Zelfborgende
flensmoer (DIN
6923)
RM

| Artikel | Afwerking | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|--------------------|-----------|---------|---------|--------------|---------|--------|---|-------|
| KLZVSB200 | - | 150 | 218 | | 1135 | 13,680 | 1 | STK |
| KLZVSB300 | - | 150 | 318 | | 1135 | 14,000 | 1 | STK |
| KLZVSB400 | - | 150 | 418 | | 1135 | 14,320 | 1 | STK |
| KLZVSB500 | - | 150 | 518 | | 1135 | 14,640 | 1 | STK |
| KLZVSB600 | - | 150 | 618 | | 1135 | 14,964 | 1 | STK |
| HDKLZVSB200 | HD | 150 | 200 | 2,0/1,25/3,0 | 1135 | 13,680 | 1 | STK |
| HDKLZVSB300 | HD | 150 | 300 | 2,0/1,25/3,0 | 1135 | 14,000 | 1 | STK |
| HDKLZVSB400 | HD | 150 | 400 | 2,0/1,25/3,0 | 1135 | 14,320 | 1 | STK |
| HDKLZVSB500 | HD | 150 | 500 | 2,0/1,25/3,0 | 1135 | 14,640 | 1 | STK |
| HDKLZVSB600 | HD | 150 | 600 | 2,0/1,25/3,0 | 1135 | 14,964 | 1 | STK |

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- HD =